

Subject Index

- Abrasive media, inspecting cleanliness of, 9-3
 - Evaluating for salt, 9-3
 - Testing for oil, 9-4
- Application of thermal spray coatings, ambient conditions required for, 7-1
 - Air temperature, humidity, and dew point, 7-1
 - Steel temperature, 7-1
- Application of thermal spray coatings, techniques for, 7-2
 - Spray angle, 7-3
 - Spray pattern, 7-2
 - Standoff distance, 7-2
- Application, sequence of thermal spray, 7-5
- Applicator, qualification of, 10-2
 - Adhesion, coating, 10-3
 - Appearance, coating, 10-2
 - Equipment setup and operation, 10-2
- Characteristics, 2-1
 - Adhesion, 2-2
 - Anodic, 2-2
 - Cathodic, 2-2
 - Corrosion resistance, 2-2
 - Density, 2-1
 - Erosion resistance, 2-1
 - Hardness, 2-1
- Coating selection, considerations in, 5-1
 - Cavitation/erosion, 5-3
 - Cost, 5-5
 - Ease of application, 5-4
 - Extremes of pH, 5-2
 - Extremes of temperature, 5-1
 - Field conditions, 5-5
 - High humidity, 5-1
 - Immersion, 5-2
 - Impact and abrasion, 5-3
 - Limits on surface preparation, 5-4
 - Maintainability, 5-5
 - Regulatory requirements, 5-4
 - Solvent exposure, 5-2
 - Special exposures, 5-3
 - Thermal cycling, 5-3
 - Ultraviolet exposure, 5-3
 - Wet/dry cycling, 5-2
- Coatings for
 - Atmospheric exposures, 5-6
 - Cathodic protection of reinforcing steel, 5-9
 - Cavitation/erosion protection, 5-10
 - Freshwater immersion, 5-6
 - High-temperature exposures, 5-7
 - Nonskid applications, 5-9
 - Partially submerged structures, 5-10
 - Seawater immersion, 5-6
 - Zebra mussel protection, 5-8
- Coverage of thermal spray coatings, 7-5
- Environment and worker protection regulations, 13-1
- Equipment, operation of arc spray, 7-4
 - Air cap selection, 7-4
 - Arc shorting control, 7-4
 - Atomization air pressure, 7-4
 - Cable length, 7-4
 - Power, 7-4
 - Voltage, 7-4
 - Wire feed rate, 7-4
 - Wire tips, 7-4
- Equipment, operation of wire and powder flame spray, 7-3
 - Air cap selection, 7-4
 - Atomization air pressure, 7-3
 - Oxygen and fuel gas flow rates, 7-3
 - Powder feed rate, 7-3
 - Wire feed rate, 7-3
- Equipment, qualification procedure, 10-1
 - Adhesion, coating, 10-2
 - Appearance, coating, 10-2
 - Uniformity of operation, 10-1
- Inspection of sealers, 9-8

- Inspection, blast cleaning, 9-2
 - Abrasive cleanliness, 9-3
 - Ambient air condition, 9-3
 - Blast air pressure, 9-4
 - Blast nozzle orifice, 9-4
 - Compressed air cleanliness, 9-3
 - Surface profile, 9-4
- Inspection, documentation of, 9-9
- Inspection, frequency of, 9-8
- Inspection, presurface preparation, 9-2
 - Grease and oil, 9-2
 - Heat affected zones, 9-2
 - Pitting, 9-2
 - Sharp edges, 9-3
 - Soluble salts, 9-3
 - Weld flux and spatter, 9-2
- Inspection, surface cleanliness, 9-4
 - Blast cleanliness, 9-4
 - Dust, 9-5
 - Grease and oil, 9-5
 - Soluble salts, 9-5
- Inspection, thermal spray, 9-1
 - Adhesion, 9-7
 - Ambient conditions, 9-6
 - Appearance of applied coating, 9-7
 - Bend testing, 9-6
 - Coating thickness, 9-6
- Job reference standard, 9-1
 - Evaluation of, 9-1
 - Preparation of, 9-1
- Maintenance of thermal spray coatings, 11-1
 - Assessing condition, 11-1
 - Repair procedures, 11-1
 - Repair sequences, 11-2
- Materials, testing of thermal spray, 3-3
 - Cast and helix, 3-3
 - Composition, 3-3
 - Surface appearance, 3-3
- Materials, thermal spray, 3-1
 - Acceptance of, 3-2
 - Certification of, 3-2
- Classification of, 3-1
- Identification and marking of, 3-3
- Manufacture of, 3-3
- Packaging of, 3-3
- Procurement of, 3-1
- Sizes of, 3-2
- Specification by product, name/manufacture, 3-1
- Processes, thermal spray application, 2-3
 - Arc spraying, 2-4
 - Detonation flame spraying, 2-4
 - Flame spraying, 2-3
 - High velocity oxygen flame spraying, 2-3
 - Plasma spraying, 2-6
 - Powder flame spraying, 2-3
 - Wire flame spraying, 2-3
- Reference samples, 9-1
 - Blast media, 9-1
 - Paint, 9-1
 - Sealer, 9-1
 - Wire, 9-1
- Safety, 12-1
 - Material safety data sheets, 12-8
 - Plans and submittals, 12-4
 - Sealing and painting, 12-4
 - Surface preparation, 12-1
 - Thermal spray procedures, 12-2
- Sealers, types of, 8-1
 - Aluminum pigmented epoxy mastic (CID A-A-3127), 8-2
 - Aluminum, silicone (TT-P-28) for high temperature, 8-2
 - Coal tar epoxy (C-200A), 8-2
 - Epoxy primer/polyurethane topcoat (CID A-A-3132), 8-2
 - Silicone alkyd for high temperature, 8-3
 - Tung-oil phenolic aluminum (TT-P-38), 8-2
 - Vinyl (V-102e, V-103c, V-106d, V-766e), 8-1
 - Vinyl-butyl wash primer (SSPC Paint No. 27)/alkyd (CID A-A-2962), 8-2
- Sealing and painting of thermal spray coatings, 8-1, 8-3
 - Characteristics of sealers, 8-1
 - Purpose, 8-1
 - Types of sealers, 8-1

Surface preparation, abrasive blast cleaning, 6-2

- Abrasive cleanliness, 6-3
- Blast media type and selection, 6-3
- Blast profile, 6-4
- Centrifugal, 6-5
- Cleaning after, 6-5
- Equipment, 6-2
- Techniques, 6-3
- Time between blasting and thermal spraying, 6-6
- With reusable media, 6-4

Surface preparation, minimizing costs, 6-6

Surface preparation, solvent cleaning, 6-1

- Hydrocarbon solvent cleaning, 6-1
- Steam cleaning, 6-1
- Water cleaning, 6-1

Surface preparation, standards and specifications, 6-7

- SSPC-SP 5 or NACE #1, 6-7
- SSPC VIS 1-89, 6-7

Surface preparation of

- Edges, 6-7
- Heat-affected zones, 6-7
- Pitted steel, 6-7

Types of thermal spray materials, 2-2

- Ceramic, 2-2
- Corrosion resistant zinc, aluminum, and zinc-aluminum alloy coatings, 2-2
- Ferrous metal alloy, 2-2
- Other, 2-2
- Polymer, 2-2
- Stellite 6, 5-9

Uses of thermal spray coatings, 2-7

- Antifoulants, 2-7
- Cathodic protection, 2-7
- Cavitation resistance, 2-8
- Corrosion protection, 2-7
- Electrical applications, 2-8
- High-temperature resistance, 2-7
- Insulation, 2-8
- Repair, 2-8
- Wear resistance, 2-7